

FH-02

Versatile LPG/CNG injection system

Part no.: LW.1 / LW.2 / LW.3 / LW.4

Standard injection system for economical gas installations. Modular design allows it to be mounted in many ways.

Types available:

FH02 4-cyl - dedicated to 4-cyl & 8-cyl engines, 4 injection channels.
FH02 3-cyl - dedicated to 3-cyl & 6-cyl engines, 3 injection channels.
FH02 2-cyl - dedicated to 4-cyl boxer engines, 2 injection channels.
Fh02 1-cyl - dedicated to engines with advanced inlet manifold systems.

Main features:

- Power supply: 12V DC
- Operational temperature range: -30 / +120 °C (-22 / +250 °F)
- Gas compatibility: LPG / CNG
- Working pressure range: 0,5 - 2,5 bar (7.25 - 36.25 psi)
- Maximum allowable pressure: 4,5 bar (65 psi)
- Coil resistance: 3 Ohm +/- 4%
- Body: aluminum (FH02-4, FH02-3, FH02-2) / brass (FH02-1)
- Opening time: 3,0 ms
- Closing time: 2,5 ms
- LPG / CNG inlet external diameter: 12 mm
- Standard valve seat diameter: 3,3 mm
- Calibration nozzle sizes available: 1,5 – 3,5 mm (0,25 mm step)
- Normally closed
- Single adapter length: 77,5 mm
- Adapter weight: 104 g
- Approvals: ECE 67R01, ECE110R00



Versatile configuration:

■ Single channel adapters



■ Distribution rail for 2/3/4 channels



www.versusgas.com

+48 25 759 42 61

info@versusgas.com

 **VERSUS**[®] 
AUTO GAS equipment

FHT Export-Import
ul. Szczecinska 16G
05-300 Minsk Mazowiecki, POLAND